RED SIGNAL AHEAD SIGN







TYPICAL BLANKOUT SIGNS





NOTES:

1. "SIGNAL AHEAD" CONTINUOUSLY LIT. "SIGNAL AHEAD" AND "RED" SHALL FLASH ALTERNATELY DURING FLASH OPERATION. FLASHING OPERATION TO BEGIN PRIOR TO TERMINATION OF HIGHWAY GREEN AS SPECIFIED. THE LEGEND "RED" IS PORTLAND ORANGE. THE LEGEND "SIGNAL AHEAD" IS LUNAR WHITE.
2. MINIMUM OF 2 LAMPS REQUIRED FOR EACH LINE OF LEGEND.
3. FIBER-OPTIC BUNDLES TO BE ARRANGED UTILIZING BIFURCATED COMBED RANDOMIZATION.
4. SIGN CASE SHALL BE FULLY GASKETED AND WATERTIGHT.
5. HINGE AND ALL HARDWARE SHALL BE STAINLESS STEEL.
6. FOR INSTALLATION ON STEEL STANDARD SEE DRAWING NO. T-34.

NEW JERSEY DEPARTMENT OF TRANSPORTATION

ELECTRICAL DETAILS

N.T.S.

"RED SIGNAL AHEAD" SIGN

T-1407

REFERENCE

BDC07D-03