

Delaware River Basin Commission

WASP Water Quality Model of the Upper Delaware for Thermal Management

Subcommittee on Ecological Flows

J. Yagecic

Presented to an advisory committee of the DRBC on February 19, 2019. Contents should not be published or re-posted in whole or in part without permission of DRBC.





SEF Charge

- * **SEF Charge**
- * **Provide recommendations to RFAC on how to ‘spend’ a volume of reservoir water to mitigate thermal stresses in the Upper Delaware**
- * **Due date *May 31, 2019***

Motivation

- * DRBC is building an Upper Delaware WASP model to facilitate evaluation of different temperature mitigation approaches
- * Could be used in conjunction with other models & methods in various stages of development: Cole Heat Flux model, Kolesar statistical model, DSS, heuristics
- * Support current and future deliberations

- * Take advantage of new tools for generating model segments
- * Take advantage of access to EPA
- * Ultimately connect to downstream for time-of-travel and other needs (Hancock train derailment)



Segmentation

- * 261 model segments, West Branch, East Branch, Beaver Kill, Mainstem Delaware
- * Upstream boundaries:
 - * Stilesville gage (West Branch)
 - * Downsville gage (East Branch)
 - * Beaver Kill at Cooks Falls (Beaver Kill)
- * Targeted segment length between 0.5 and 1 km
- * Trapezoidal channels with hydraulic properties that mimic stage discharge relationships at gages


Model Properties

Segments

- * NHDplus (via BASINS)
- * Width
- * Length
- * Bed slope
- * Roughness
- * Populated for model run period 2008 through November 2018
- * Calibration focus 2018
- * Ungaged tributaries estimated using QPPQ similar to BaSE

Stage Discharge Relationships and Manning's Equation

WEST BRANCH DELAWARE RIVER AT HALE EDDY NY
Computed 2019-02-08




$$V = \frac{R_h^{2/3} S^{1/2}}{n}$$

$$Q = VA$$



$$V \approx aQ^b$$

$$\text{Depth} \approx cQ^d$$



DELAWARE RIVER AT LORDVILLE NY
Computed 2019-02-08



Temperature Calibration Status



Temperature Calibration Status



WASP Thermal Model – Next Steps

- * Add WWTPs at Deposit and Hancock (maybe others)
- * Thermal calibration
- * Run with Cannonsville discharge at sustained low flow to estimate number of heat stress days in absence of coldwater inflow
- * Evaluate default protocol for use of thermal pool
- * Evaluate alternative protocols for use of thermal pool