Crushed Stone, Sand & Gravel

ATTACHMENT 1: Coarse Aggregate Standard Sizes and Sampling

			Т	able	901.0	3-1 St	andar	d Size	s of C	oarse	Aggre	gate				
				Am	ounts	finer t	han e	ach la	borato	ory sie	ve, pe	rcenta	ge by	/ weig	ht	
No.	Nominal Size	4"	3- 1/2"	3"	2- 1/2"	2"	1- 1/2"	1"	3/4"	1/2"	3/8"	No. 4	No. 8	No. 16	No. 50	No. 100
1	3-1/2" - 1- 1/2"	100	90- 100		25-60		0-15		0-5		<u> </u>	I	<u> </u>	<u> </u>		
2	2-1/2" - 1- 1/2"			100	90- 100	35-70	0-15		0-5							
3	2" - 1"			<u> </u>	100	90- 100	35-70	0-15		0-5						
4	1-1/2" - 3/4"				1	100	90- 100	20-55	0-15		0-5					
5	1" - 1/2"					I	100	90- 100	20-55	0-10	0-5					
57	1" - No. 4						100	95- 100		25-60		0-10	0-5			
67	3/4"- No. 4						1	100	90- 100		20-55	0-10	0-5			
7	1/2" - No. 4							1	100	90- 100	40-70	0-15	0-5			
8	3/8" - No. 8								<u> </u>	100	85- 100	10-30	0-10	0-5		
9	No. 4 - No. 16									<u>I</u>	100	85- 100	10- 40	0-10	0-5	
10	No. 4 - No. 200										100	85- 100		1	<u> </u>	10-30

Table 901.03-2 Coarse Aggregate Sampling								
Coarse Aggregate, No.	Sample Size (pounds)	Frequency						
1	150	1000 tons or 830 cubic yards						
2	100	1000 tons or 830 cubic yards						
3	90	1000 tons or 830 cubic yards						
4	70	1000 tons or 830 cubic yards						
5 & 57	50	500 tons or 415 cubic yards						
67	30	500 tons or 415 cubic yards						
7	20	250 tons or 200 cubic yards						
8, 9, & 10 (stone sand)	10	250 tons or 200 cubic yards						